


Variants: "M"; "G" threads



Designation: 30A(C)...X237HM(G)

For ports measures see table at 30A(C)...X163H

Type	Displacement cm ³ /rev	Flow		Pressure P _{nom} bar	max Speed n rpm	Dimension								
		at 1500 rpm l/min	at max rpm l/min			Inlet			Outlet					
						A mm	B mm	E mm	d mm	F mm	E mm	d mm	F mm	
30A(C)20X237H	20	28,2	56,4	250	3000	56,1	116,7	40	M8	19	40	M8	19	
30A(C)22,2X237H	22,5	31,7	63,5	250	3000	57,6	119,7							
30A(C)25X237H	25	35,3	70,5	250	3000	58,3	121,1							
30A(C)28X237H	28	39,5	79,0	250	3000	60,2	124,7							
30A(C)32X237	32	45,1	75,2	250	2500	62,0	128,3	51	M10	27	40	M8	19	
30A(C)32X237H	32	45,1	90,2	250	3000	66,5	137,3							
30A(C)36X237	36	50,8	84,6	250	2500	63,5	131,4							
30A(C)36X237H	36	51,3	95,8	250	2800	68,0	140,5							
30A(C)42X237	42	59,9	91,8	230	2300	66,3	137,0	51	M10	27	40	M8	19	
30A(C)42X237H	42	59,9	99,8	230	2500	70,8	146,1							
30A(C)46X237H	46	65,6	100,5	230	2300	72,7	149,8							
30A(C)50X237H	50	71,3	99,8	200	2100	74,5	153,4							
30A(C)55X237H	55	78,4	91,4	200	1750	76,7	157,9	51	M10	27	40	M8	19	
30A(C)60X237H	60	85,5	99,8	180	1750	78,7	162,4							